

Compact 4-way Cassette Indoor Unit



- **Compact Design for Easy Installation**

Units maintain the uniform length and width with consistent ceiling opening and panel dimension, convenient for design and installation;

- **Ultra-low noise operation**

DC inverter motor can realize stepless speed regulation to lower noise. Indoor unit can be set to work under auto quiet mode via wired controller.

- **Intelligent drainage device**

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

Compact 4-way Cassette Indoor Unit

50/60 Hz

Model			GMV-ND22T/B-T	GMV-ND28T/B-T	GMV-ND36T/B-T	GMV-ND45T/B-T	GMV-ND50T/B-T	GMV-ND56T/B-T
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5	5.6
	Heating	kW	2.5	3.2	4	5	5.6	6.3
Power supply	V/Ph/Hz		220~240/1/50 & 208~230/1/60					
Power consumption	W		35	35	35	45	45	45
Airflow volume(H/M/L)	m ³ /h		600/500/400	600/500/400	600/500/400	700/600/480	700/600/480	700/600/480
	CFM		355/295/235	355/295/235	355/295/235	410/355/283	410/355/283	410/355/283
Rated Current ²	Cooling	A	0.4	0.4	0.4	0.5	0.5	0.5
	Heating	A	0.4	0.4	0.4	0.5	0.5	0.5
	Water Heating	A	/	/	/	/	/	/
Sound pressure level(H/M/L)	dB(A)		46/39/35	46/39/35	46/39/35	47/43/38	47/43/38	47/43/38
Connecting pipe diameter	Liquid	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52
	Gas	mm	Φ9.52	Φ9.52	Φ12.7	Φ12.7	Φ12.7	Φ15.9
Drain pipe	External dia.	mm	25	25	25	25	25	25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5
Main Body	Dimension (WxDxH)	Outline	mm	596x596x240	596x596x240	596x596x240	596x596x240	596x596x240
	Net weight/Gross weight	Package	mm	773x733x300	773x733x300	733x733x300	733x733x300	733x733x300
			kg	20.5/25.5	20.5/25.5	20.5/25.5	20.5/25.5	20.5/25.5
Panel	Dimension (WxDxH)	Outline	mm	650x650x50	650x650x50	650x650x50	650x650x50	650x650x50
	Net weight/Gross weight	Package	mm	763x763x105	763x763x105	763x763x105	763x763x105	763x763x105
			kg	3.5/5.0	3.5/5.0	3.5/5.0	3.5/5.0	3.5/5.0
Loading quantity	40'GP	set	267	267	267	267	267	267
	40'HQ	set	288	288	288	288	288	288